



Metallic Liquid Tight Conduit (YF-706)

HEAVY DUTY FLEXIBLE PVC COVERING
(WITH SMOOTH WIPE-CLEAN SURFACE)
KEYED INTO THE CORRUGATIONS

GALVANIZED STEEL STRIP
HELICALLY WOUND WITH
NYLON SEALING CORD



UNIQUE "Deli-LOK" LOCKING & SEALING MECHANISM
FOR INCREASED STRENGTH AND MOISTURE TIGHTNESS



SMOOTH PVC COVERING
GALVANIZED STEEL STRIP
("Deli-LOK" PROFILE)
NYLON SEALING CORD
PACKING



- *Liquid-tight
- *High tensile strength
- *Good Mechanical Protection

Type	Trade Size	I.D. (mm)		O.D. (mm)		Min. Bending Radius (mm)	Meters/Coil
		MIN.	MAX.	MIN.	MAX.		
YF-70602	1/4"	6.2	6.7	11.4	11.9	50	100
YF-70603	3/8"	12.5	13.0	17.8	18.3	60	50
YF-70604	1/2"	16.1	16.6	21.3	21.8	80	50
YF-70606	3/4"	20.7	21.3	25.9	26.4	100	30
YF-70610	1"	26.3	26.8	33.3	33.8	150	30
YF-70612	1-1/4"	35.0	35.5	42.6	43.1	180	20
YF-70614	1-1/2"	40.0	40.5	47.6	48.0	220	20
YF-70620	2"	51.0	51.5	60.3	60.8	250	15
YF-70624	2-1/2"	63.0	63.7	72.2	73.0	300	10
YF-70630	3"	78.0	78.8	88.2	89.0	450	10
YF-70640	4"	101.8	102.8	113.2	114.0	600	5
5" & 6" large size liquid tight conduits are constructed with a fully interlocked strip for added strength and to prevent unraveling. Resistant to most industrial oils, acids and vapors.							
YF-70650	5"	126.0	128.0	133.0	135.0	750	5
YF-70660	6"	149.0	151.0	156.0	158.0	900	5

Flexible Liquid-tight Metal conduit (*Liquid Tight Conduit*) is ideal when used with liquid tight conduit fittings for electrical wiring applications where a high degree of liquid tightness is required.